


UNAUTHORIZED USE OF THIS
DRAWING IS STRICTLY PROHIBITED

DAR	REV	DESCRIPTION	APPVD	DATE
1034	A	INITIAL RELEASE	TJD	12-05



NOTES

- 1. CONNECTORS J1 & 2:
TYPE N-F
- CONNECTORS J3 & 4:
TYPE N-F

ELECTRICAL SPECIFICATIONS

FREQUENCY:	20 – 500 MHz.
INSERTION LOSS:	0.3dB MAX.
VSWR:	1.20:1 MAX.
COUPLING:	50.0 ±1.0dB
DIRECTIVITY:	>20dB
COUPLED FLATNESS:	±0.50dB MAX.
POWER:	1000 WATT

MATERIAL AL. ALLOY 6061-T651	DWN DG	DATE 12/05		
	ENG TJD	DATE 12/05		
FINISH CHEM FILM CLEAR IRRIDITE	MANUF TP	DATE 12/05	TITLE OUTLINE, DUAL DIRECTIONAL COUPLER, 20-500 MHz., 50dB, 1KW	
	CAGE CODE: 437R2		P/N IPP-3001	
TOLERANCE IN [MM]	.XXX ±.005 .XX ±.02 ANG. ±1/2°	SHEET OF 1 1		SCALE 1:1