


UNAUTHORIZED USE OF THIS
DRAWING IS STRICTLY PROHIBITED

DAR	REV	DESCRIPTION	APPVD	DATE
1504	A	INITIAL RELEASE	DG	8-08
2059	B	SEE DAR	DG	9-09



NOTES

- J1 - J4: 0.050 X 0.005 SILVER TABS
GND: 0.120 X 0.005 SILVER TABS

ELECTRICAL SPECIFICATIONS

- FREQUENCY: 100 - 1000 MHz.
- INSERTION LOSS: <0.25dB
- VSWR: <1.25:1
- COUPLING: 50.0 ±1.0dB
- DIRECTIVITY: > 20dB
- COUPLED FLATNESS: ±0.50dB
- POWER: 200 WATT

MATERIAL AL. ALLOY 6061-T651	DWN S.Cornell	DATE 8-14-08	
	ENG TJD	DATE 8-08	
FINISH CHEM FILM CLEAR PER MIL-DTL-5541, TYPE 2, REV F, CLASS 3 ROHS COMPLIANT	MANUF TP	DATE 8-08	TITLE DUAL DIRECTIONAL COUPLER 100 - 1000 MHz. 200 WATT, 50 dB
	CAGE CODE: 437R2		P/N IPP-3064
TOLERANCE .XX ±.02 .XXX ±.010 ANG. ±1/2°	SHEET OF 1 1	SCALE .75:1	